



SeeSnake® Compact DSL Series

No moving parts. Maximum Uptime.



RIDGID® SeeSnake® Compact series camera reels deliver big performance in a small package. Now Equipped with Digital Self-Leveling, which delivers crisp, clear and upright image at all times with the added benefit of no moving parts. Compatible with the SeeSnake CS6x Versa digital reporting monitor for fast set-up and easy viewing. The built-in Wi-Fi and Bluetooth make live streaming and inspection to an iOS™ or Android™ device simple with the free HQx Live app.

- Digital Self Leveling: Our most advanced self-leveling camera has no moving parts, which maximizes uptime while always retaining a smooth & upright on screen image
- TruSense™ Technology: Features two-way communication between the camera and a CSx series Wi-Fi enabled monitor
- High Dynamic Range Image Sensor: Provides bright, saturated images with improved detail, even in difficult lighting conditions
- TiltSense Inclinometer: Lets you know camera's degree of tilt inside the pipe when used with a CSx series monitor
- Use with the SeeSnake CS6x Versa to create the optimal viewing angle and for fast, efficient job setup



SPECIFICATIONS

- Light Source High-Intensity LED
- Push Cable Length..... 131' (40 m)
- Push Cable Minimum Bend Radius..... 2.5" (64 mm)/3" (76 mm)
- 512 Hz Sonde High-power Flexmitter®
- Dimensions (LxWxH)..... 25" x 14" x 17"
(626 mm x 360 mm x 429 mm)
- Operating Temperature 14°F to 122°F (-10°C to 50°C)
- Storage Temperature..... 14°F to 158°F (-10°C to 70°C)
- Ingress Protection (without Monitor)..... IPx6

COMPACT SERIES QUICK COMPARISON GUIDE

CAMERA REEL		CAMERA HEAD	PUSH CABLE	MINIMUM BEND RADIUS	LINE CAPACITY
Compact C40 DSL Camera Reel		25 mm (1") Self-Leveling w/TruSense Technology	131' (40 m)	2.5" (64 mm)	1.5" - 6" (38 mm - 152 mm)
Compact M40 DSL Camera Reel		25 mm (1") Self-Leveling w/TruSense Technology	131' (40 m)	3" (76 mm)	1.5" - 8" (38 mm - 203 mm)

ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT	
		(lb.)	(kg)
82143	Compact C40 DSL (Reel Only)	17.2	7.8
70043	Compact C40 DSL w/CS6x Versa Monitor	22.1	10.0
70053	Compact C40 DSL w/CS6x Versa Monitor, Battery and Charger	25.1	11.4
82138	Compact M40 DSL (Reel Only)	22.0	9.8
69763	Compact M40 DSL w/CS6x Versa Monitor	26.9	12.0
69998	Compact M40 DSL w/CS6x Versa Monitor, Battery and Charger	29.9	13.6

ACCESSORIES

CATALOG NO.		DESCRIPTION
63868	5	Kit, Pipe Guide 25mm Camera Head (various sizes)
46708	2	Pipe Guide, 85mm OD, 25mm Camera Head
46713	2	Pipe Guide, 125mm OD, 25mm Camera Head
35338	2	Pipe Guide, 45mm OD, 25mm Camera Head
40598	2	Pipe Guide, 60mm OD, 25mm Camera Head
88392	10	Pipe Guide (Wire Clip), 60mm OD, 25mm Cam Head
67312	20	Star Guide, 99mm OD, 25mm Cam Head
47793	1	Camera Head Guide, 36mm OD, 25mm Camera Head
17553	1	Spanner Wrench, 25 mm



RIDGID.COM/seesnake

All sales subject to Ridge Tool Company Terms and Conditions of Sales. Catalog Sheet No. R-25-D (625) Effective Date: July 1, 2025
©2025 Ridge Tool Company



HDR

High Dynamic Range (HDR) image sensor offers clear in-pipe imaging.



TiltSense™

Data Sensor displays camera's angle in pipe.



Scan for more information on HQx Live

